

## Vintage Series - 1/2" 5V Crimp

METAL	MAX. WIDTH	SUBSTRATE	FPA	HZVZ	TDI	UL LISTING	FASTENER SPACING	NOTES	UPLIFT PRESSURE
.032" Alum	21"	15/32" plywood	✓		✓	✓	10"		168.5
.032" Alum	24"	15/32" plywood	✓	✓	✓	✓	12"		183.5
.032" Alum	24"	15/32" plywood	✓		✓	✓	12"		183.5
.032" Alum	24"	15/32" plywood	✓	✓	✓	✓	16"		116.25
26ga Steel	24"	15/32" plywood	✓	✓	✓	✓	6"		168.5
26ga Steel	24"	15/32" plywood	✓		✓	✓	6"		228
26ga Steel	24"	15/32" plywood	✓	✓	✓	✓	8"		206
26ga Steel	24"	15/32" plywood	✓		✓	✓	8"		206
26ga Steel	24"	15/32" plywood	✓	✓	✓	✓	12"		104.75
26ga Steel	24"	15/32" plywood	✓		✓	✓	12"		116
26ga Steel	24"	15/32" plywood	✓	✓	✓	✓	16"		117.75
26ga Steel	24"	15/32" plywood	✓		✓	✓	16"		101
26ga Steel	24"	15/32" plywood	✓		✓	✓	16"		86

This list represents Metal Roof Supply's best effort to summarize current FL Product Approvals and TDI listings and is subject to change without notice. For the most up to date information, visit the [Florida Building Commission](#) and [Texas Department of Insurance](#) websites.