

Legacy S100-NF - 1" SNAP-LOK NAILSTRIP

METAL	MAX. WIDTH	SUBSTRATE	FPA	HZVZ	TDI	UL LISTING	CLIP SPACING	NOTES	UPLIFT PRESSURE
.032" Alum	16"	15/32" plywood	✓		✓	✓	5"	B, C	153.5
.032" Alum	16"	15/32" plywood	✓	✓	✓	✓	6"	A, B	175
.032" Alum	16"	15/32" plywood	✓		✓	✓	6"	A	168.5
.032" Alum	16"	15/32" plywood	✓		✓	✓	10"		86
24ga Steel	16"	15/32" plywood	✓		✓	✓	6"	A	206
26ga Steel	16"	15/32" plywood	✓		✓	✓	5"	C	108.5
26ga Steel	16"	15/32" plywood	✓	✓	✓	✓	6"	A	116
26ga Steel	16"	15/32" plywood	✓	✓	✓	✓	6"	A, B	176
26ga Steel	16"	15/32" plywood	✓		✓	✓	10"		78.5

Notes: A - Fasteners through metal flange, not prepunched slots, B - WITH sealant applied to base of male leg, C - Over self-adhering underlayment

This list represents Metal Roof Supply's best effort to summarize current FL Product Approvals and TDI listings and is subject to change without notice. For the most up to date information, visit the [Florida Building Commission](#) and [Texas Department of Insurance](#) websites.